



# RMTDU



3U 19" Triple-screen Rack-mount display

# Technical Specifications

PRODUCT	RMTDU
DISPLAY	3X 19" SXGA 1280 X 1024
VIEWING ANGLE	DISPLAYS TILT ~15° FROM VERTICAL
PORTS	1X VGA, 1X DVI, 1X DP, AND 2X USB
POWER SUPPLY	115/230 VAC, 50/60 HZ, 75W MAX
KEYBOARD & MOUSE	101 KEYS BACKLIT KEYBOARD WITH TOUCHPAD AND ADJUSTABLE BRIGHTNESS + CAPACITIVE TOUCHPAD
DIMENSIONS	HEIGHT: 3U - 5.13" (130MM), WIDTH: 17.76" (451MM), DEPTH: 25.8" (655MM)
WEIGHT	~58LBS (26KG)
TEMPERATURE	MIL-STD-810E (501.4, 502.4), OPERATING: 0 ~ 50°C, NON-OPERATING: -40 ~ 70°C
HUMIDITY	MIL-STD-810E (507.2), RELATIVE HUMIDITY: 5% TO 95% OPERATING, NON-CONDENSING

\* The technical specifications are an example of the system's capabilities. They can be customized specifically for your needs. If you have any questions, feel free to contact one of our sales representatives.



## Headquarters - USA

ACME Portable Machines, Inc.  
1330 Mountain View Circle,  
Azusa, CA, 91702, USA  
Tel: +1 626.610.1888  
Fax: +1 626.610.1881  
[www.acmeportable.com](http://www.acmeportable.com)

## Germany

ACME Portable Computer GmbH  
Benzstraße 15,  
76185 Karlsruhe, Germany  
Tel: +49.721.570.4530  
Fax: +49.721.570.45329  
[www.acmeportable.de](http://www.acmeportable.de)

## Taiwan

ACME Portable Corp.  
5F, No 25, Wuquan 3rd Road,  
Wugu Dist., New Taipei City 248,  
Taiwan R.O.C  
Tel: +886.2.2298.3636  
Fax: +886.2.2298.3737  
[www.acmeportable.com.tw](http://www.acmeportable.com.tw)