



RMDDU 17



The RMDDU 17 is a 2U 17" dual screen rackmount with 2 ports.

Technical Specifications

PRODUCT	RMDDU 17
DISPLAY	DUAL 17.3" FULL HD 1920 X 1080, 16:9 DISPLAY
VIEWING ANGLE	DISPLAYS TILT ~15° FROM VERTICAL
PORTS	2X USB 2.0 INPUTS ON FRONT + 2X USB 2.0 INPUTS ON REAR ANALOG VGA, DVI-D, DISPLAY PORT
POWER SUPPLY	115/230 VAC, 50/60HZ, 100W MAX
KEYBOARD & MOUSE	101 KEYS BACKLIT KEYBOARD WITH TOUCHPAD AND ADJUSTABLE BRIGHTNESS. RESISTIVE TOUCHPAD OPTIONAL: WATERPROOF KEYBOARD
DIMENSIONS	HEIGHT: 2U - 3.46" (88MM) WIDTH: 17.76" (451MM) DEPTH: 25.89" (657.6MM) RACK DEPTH: 24" (609.6MM)
WEIGHT	~42 LBS (19KG)
TEMPERATURE	MIL-STD-810E (501.4, 502.4), OPERATING: 0 ~ 50°C, NON-OPERATING: -40 ~ 70°C
HUMIDITY	MIL-STD-810E (507.2), RELATIVE HUMIDITY: 5% TO 95% OPERATING, NON-CONDENSING
ALTITUDE	MIL-STD-810E (500.3), OPERATING: 15,000 FT (4571.8 M), NON-OPERATING: 40,000 FT (12,192 M)
VIBRATION	MIL-STD-810E (514.4) OPERATING: 10 TO 500 HZ 1.04 G (RMS)
SHOCK	MIL-STD-810E (516.4), OPERATING: 15 G, 8 MS 1/2 SINE, NON-OPERATING: 40 G, 8 MS 1/2 SINE
DROP	4" STAND ALONE, 39" TRANSIT DROP IN TRANSIT CASE

* The technical specifications are an example of the system's capabilities. They can be customized specifically for your needs. If you have any questions, feel free to contact one of our sales representatives.



Headquarters - USA

ACME Portable Machines, Inc.
1330 Mountain View Circle,
Azusa, CA, 91702, USA
Tel: +1 626.610.1888
Fax: +1 626.610.1881
www.acmeportable.com

Germany

ACME Portable Computer GmbH
Benzstraße 15,
76185 Karlsruhe, Germany
Tel: +49.721.570.4530
Fax: +49.721.570.45329
www.acmeportable.de

Taiwan

ACME Portable Corp.
5F, No 25, Wuquan 3rd Road,
Wugu Dist., New Taipei City 248,
Taiwan R.O.C
Tel: +886.2.2298.3636
Fax: +886.2.2298.3737
www.acmeportable.com.tw